

VRM 175 / 250 / 270

VRM pumps are engineered to excel in a variety of demanding applications, including Sludge Transfer, Digester Feed, Grit Removal, Food Waste Management.

DESIGNED FOR PERFORMANCE

Performance & Durability:

- ✓ **24-Hour Operation:** Designed for continuous use, ensuring reliability around the clock.
- ✓ **Slow Speed, Quiet Operation:** Enjoy the benefits of quieter performance without sacrificing efficiency.
- ✓ **Superior Suction Lift:** The slow-speed operation coupled with a powerful suction lift ensures maximum wear resistance, making VRM pumps ideal for handling aggressive waste products.

Economic & Maintenance Advantages:

- ✓ **Outstanding Whole-Life Costs:** Achieve significant cost savings throughout the lifespan of the pump.
- ✓ **Minimal Maintenance:** Built to last with extremely low maintenance requirements.
- ✓ **Reduced Spare Part Needs:** Fewer spare parts are needed, reducing downtime and operating costs.

Experience the quiet efficiency, durability, and cost-effectiveness of VRM pumps for all your wastewater and food waste applications.

VRM RANGE



**RELIABLE, QUIET &
EFFICIENT PUMPING
SOLUTIONS**

Model	L/s	l/m	M ³ / Hr	Pressure Bar
175	1.50 – 3.50	90 – 210	5.40 – 12.60	0 – 7
250	4.17 – 6.67	250 – 400	15.00 – 24.00	0 – 7
270	4.50 – 8.00	270 – 480	16.20 – 28.80	0 – 7



PRESSURE
RANGE
0-7BAR



FLOW
LTRS/MIN
UP TO 480



QUIET AND
SLOW SPEED
OPERATIONS



PASS
THROUGH
OBJECTS OF
75MM



SUCTION
VACUUM UP
TO 0.85BAR

Call For Details

01782 510 051

